

Barcode-reader

# SUNMI 2D Handheld Scanner

- Equipped with a high-performance imaging chip, that captures even the shakiest frames, this scanner has a high motion tolerance that doesn't compromise on quality.
  - The ultra-quick decoding algorithm is the true definition of speed as it accurately identifies folded, colored and even distorted bar codes for easy accessibility.
  - The scanner briefly vibrates to let you know when a scan is complete so you never miss a code.
  - With looks that follow the latest design trends, the scanner enhances your store's image.
  - Comes with a three-year warranty(which even covers the built-in wire rods)
- \*Does not cover physical damage



Scanning Barcode



Mobile Payment



Drop-Proof



Plug and Play

## SUNMI 2D Handheld Scanner

### Technical specifications

<p><b>OS</b> OS Windows/IOS Android/Linux</p>	<p><b>Image sensor</b> CMOS</p>	<p><b>Pixel</b> 640*480</p>	<p><b>Reading precision</b> ≥3mil</p>	<p><b>Reading depth of field</b> EAN13 (13mil) 55mm-300mm QR CODE (15mil) 35mm-190mm</p>
<p><b>Lighting</b> White LED</p>	<p><b>External dimension</b> 160*95*71mm</p>	<p><b>Prompt method</b> Buzzer, vibrator, LED prompt</p>	<p><b>Focusing</b> Red light LED 625nm</p>	<p><b>Communication interface</b> USB 2.0 TypeA male connector</p>
<p><b>Field of view angle</b> Horizontal 45° Vertical 34°</p>	<p><b>Adapter</b> Operating voltage: DC5V±5% Operating current: &lt;500mA</p>	<p><b>Symbol contrast</b> ≥30%</p>	<p><b>Environment</b> Operating temperature: -10°C~50°C Storage temperature: -40°C~70°C Relative humidity: 5%~95% (no condensation) Electrostatic protection: ±8kV (direct discharge) ±15kV (air discharge) Drop height:1.2 meters</p>	<p><b>Barcode sensitivity</b> Inclined ±50° / Rotary 360° / Deflected ±50°</p>
<p><b>Symbologies</b> 1D: Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand 2D: PDF417, QR Code, Data Matrix</p>				

Note:  
1. The actual scan depth and angle depends on the operating environment and the size of the barcode, making it necessary to adjust the relative positioning of the device and the document or device containing the barcode to ensure a correct reading  
2. Actual product specifications when sold take precedence over what may be listed at this catalogue; Any changes may be made without prior notification